

Wayfinding and ADA-compliant signage.

Tactile signage with Grade 2 Braille, ADA pictograms, room IDs, directionals, and code signs — mounted to ADA §703 specifications. Designed for hospitals, campuses, hotels, and Class A corporate environments.

Specification notes

ADA §703 mounting heights

Tactile characters between 48 and 60 inches above the finished floor, measured to the baseline of the lowest and highest tactile characters. The sign mounts on the latch side of the door, clear of the door swing, with a clear 18-by-18-inch floor space centered on the tactile characters. Our installers carry an ADA gauge; tolerances are not eyeballed.

Federal vs state standards

Federal ADA applies nationwide; some jurisdictions (California, Texas, New York) add stricter requirements on character height, pictogram dimensions, and finish reflectivity. We spec to the strictest of federal-plus-state, never the loosest, so the same sign passes inspection in every market.

Multi-building campuses

Campus wayfinding is one of our highest-leverage scopes — measured drawings, hierarchy decisions (primary/secondary/tertiary), code review, fabrication, and install coordinated by one PM so the signs read as a system, not a patchwork. Healthcare and higher-education campuses are routine.

One spec, fabricated and installed in every U.S. market.

Send the brief and a project manager returns an itemized estimate inside 48 hours — signavero.com.